

Vertical Pressure steam sterilizer



FSF-28HD



FSF-35HD/50HD/75HD/100HD

Characteristics:

1. Fully stainless steel structure.
2. Hand wheel type of quick-open door structure.
3. Door safety lock system.
4. Digital display of working status, touch of key.
5. Self-inflating type seal.
6. Over temperature & over pressure auto-protection.
7. Safe protection of water lacking.
8. Automatically shut off with beep reminding after sterilization.
9. Auto discharge the cool air, and steam discharging auto matically after sterilization.
10. Used for sterilization of medical instruments, medical cotton products.
11. Fully stainless steel SUS304/AISI 304 -3mm.
12. 24 months warranty.
13. Possible to install drying system according request.

Main Technical Parameters:

Model	FSF-28HD	FSF-35HD	FSF-50HD	FSF-75HD	FSF-100HD
Capacity	28L (Φ270×500)mm	35L (Φ318×450)mm	50L (Φ340×550)mm	75L (Φ400×600)mm	100L (Φ440×650)mm
Working pressure	0.22Mpa				
Working temperature	134°C				
Max. working pressure	0.23Mpa				
Heat average	±1°C				
Timer	0~99min or 0~99hour59 min				
Temp. range	105°C~134°C				
Power	2KW/ AC220V.50Hz	2.5KW/ AC220V.50Hz	3KW/ AC220V.50Hz	4.5KW/AC220V.50Hz	
Exterior size	400×370×700mm	450×450×1010mm	510×470×1130mm	560×560×1120mm	540×560×1250mm
Packing size	440×320×750mm	570×550×1150mm	590×590×1280mm	650×630×1280mm	680×630×1370mm
G.W/N.W	26/23kg	72kg/56kg	88kg/68kg	100kg/80kg	110kg/85kg