

Horizontal Cylindrical Pressure Steam Sterilizer



Features:

- * Drying function.
- * Interlock function.
- * Automatic sterilization process.
- * 304 stainless steel material chamber.
- * Safety valve for over pressure protection.
- * Over-temperature, over-pressure protection device.
- * Water level sensor. The power will be cut-off automatically in case of low water level.

Technical Parameters:

Model	BKQ-H150	BKQ-H200	BKQ-H300	BKQ-H400	BKQ-H500
Capacity	150L	200L	280L	400L	500L
Chamber Size(mm)	φ440*1000	φ515*1000	φ600*1000	φ700*1100	φ700*1300
Working Pressure	0.22MPa				
Working Temp.	134℃				
Temperature Range	40~134℃				
Sterilization Time	0~60 min				
Drying Time	0~60 min				
Temp. Accuracy	±2℃				
Power Consumption	9KW		12KW	18KW	
Power Supply	220V/380V, 50/60Hz		380V, 50Hz		
External Size (W*D*H) mm	1400*600*1300	1400*670*1650	1400*770*1780	1430*880*1830	1800*900*1820
Packing Size (W*D*H) mm	1550*750*1850	1560*820*1850	1680*920*2100	1600*1050*2100	1850*1050*2100
Gross Weight(kg)	320	350	465	530	580