

Portable Pressure Steam Sterilizer

Characteristics:

1. Fully stainless steel structure.
2. Hand wheel type of quick-open door structure.
3. Indicator light indicates working state.
4. Double scale indication pressure gauge.
5. Time scope: 0~60min.
6. Automatically shut off with beep reminding after sterilization.
7. Electric heated.
8. Easy to operate, safe and reliable.



Main Technical Parameters:

| Model | Capacity | Working pressure | Working temperature | Temp. range | Max. safety pressure | Timer range | Heat average | Power | Packing size | G.W/N.W |
|-----------|----------|------------------|---------------------|-------------|----------------------|-------------|--------------|-----------------|---------------|---------|
| FSF-18LDJ | 18L | 0.14-0.16MPa | 126°C | 105-126°C | 0.165Mpa | 0-60min | ≤ ±1°C | AC220V.50Hz/2Kw | 410×410×520mm | 18/16KG |
| FSF-24LDJ | 24L | | | | | | | | 410×410×630mm | 20/18KG |

Portable Pressure steam Sterilizer (Electric or LPG heated)

Characteristics:

1. Fully stainless steel structure.
2. Electric or LPG heated.
3. Double scale indication pressure gauge.
4. Easy to operate, safe and reliable.



Main Technical Parameters:

| Model | Capacity | Working pressure | Working temperature | Max. safety pressure | Power | Packing size | G.W/N.W |
|----------|----------|------------------|---------------------|----------------------|-----------------|---------------|---------|
| FSF-18LM | 18L | 0.14-0.16MPa | 126°C | 0.165Mpa | AC220V.50Hz/2Kw | 410×410×430mm | 16/14KG |
| FSF-24LM | 24L | | | | | 410×410×550mm | 17/15KG |