LAUDA Aqualine

The universal water baths for the laboratory from 25 up to 95 °C











Application examples

- Preparation of medical samples for analysis
- Temperature control of cytological samples
- Pre-thermostating of samples for spectroscopic tests
- Use in colleges and education

Reliable, compact and ergonomic

The LAUDA Aqualine water baths offer an affordable entry into laboratory thermostating. The equipment range for basic applications in the laboratory stands out for its simple operation with digital LED display and high reliability. The devices have no circulating pumps and no

fittings within the bath. Consequently, they are corrosion-resistant, easy to clean or disinfect, and provide maximum use of internal bath space. The heating elements housed under the bath vessel ensure homogenous temperature distribution without localised overheating.

Your advantages at a glance



The Aqualine advantages

Your benefits




- Heating of the bath bottom across the entire base
- Patented low-level protection, minimum fill level of only 2 cm
- Excellent temperature homogeneity in the bath and optimum use of the internal space
- Bath operation almost independent of the fill level



- Recessed operating elements
- Luminous digital LED display
- Controller electronics integrated into the housing
- Dirt and drip-proof electronics
- Easy operation
- Smallest possible unit footprint



- No heaters, sensors or other fittings in the bath vessel
- Easy-clean interior
- No niches for hidden growth of germs
- Full use of the bath



- Transparent polycarbonate gable covers removable without tools are a standard feature
- Optimised roof shape


- Easy and quick visual inspection of the samples in the bath
- Easy cleaning, no height restrictions
- Prevents sample contamination from condensation

LAUDA Aqualine

Aqualine Water baths

The LAUDA Aqualine water baths are available in five different sizes. Depending on the size and the quantity of the samples, the user has the right bath depth or opening for his application at his disposal. All the baths are made from moulded stainless steel, and do not have any fittings. As a result, the interior is used to its full advantage, and the number of samples per bath is maximised. Above all, the LAUDA Aqualine is designed for the requirements of biological, medical and biochemical laboratories. Thanks to the patented heating concept, the baths also achieve a high level of temperature homogeneity.

Heating curves Heat transfer liquid: Water, bath closed



① AL 2 ② AL 5 · AL 12 ③ AL 18 ④ AL 25

Temperature range 25...95 °C

Standard accessories

Transparent polycarbonate gable cover





All technical data from page 88 Other power supply variants on page 98

| 290 mm | 290 mm | 325 mm | 325 mm | 375 mm |
|--------|--------|--------|--------|--------|

| Technical features | | AL 2 | AL 5 | AL 12 | AL 18 | AL 25 |
|---------------------------------|----|------------|-------------|-------------|-------------|-------------|
| Working temperature range | °C | 2595 | 2595 | 2595 | 2595 | 2595 |
| Temperature stability at 37 °C | ±Κ | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 |
| Heater power | kW | 0.5 | 0.5 | 1.0 | 1.2 | 1.2 |
| Bath volume | L | 0.91.7 | 15 | 212 | 318 | 325 |
| Bath opening/Bath depth | mm | 300x151/65 | 300x151/150 | 329x300/150 | 505x300/150 | 505x300/200 |
| Cat. No. 230 V; 50/60 Hz | | LCB 0723 | LCB 0724 | LCB 0725 | LCB 0726 | LCB 0727 |

Aqualine accessories

Test tube racks

Polypropylene up to 95 °C

| CatNo.: | Description | Qty. Tubes | Ø mm |
|--------------|--|---------------|------|
| UE 041 | rack white | 21 | 30 |
| UE 040 | rack white | 24 | 25 |
| UE 039 | rack white | 40 | 20 |
| UE 042 | rack white | 60 | 16 |
| UE 037 | rack white | 90 | 13 |
| UE 047 | rack yellow | 21 | 30 |
| UE 046 | rack yellow | 24 | 25 |
| UE 045 | rack yellow | 40 | 20 |
| UE 048 | rack yellow | 60 | 16 |
| UE 043 | rack yellow | 90 | 13 |
| suitable for | 1 x in AL 5 2 x in AL 12 4 x in AL 18, AL 29 | 5 | |



Test tube rack

Stainless steel up to 150 °C


| CatNo.: | Description | Qty. Tubes | Ø mm | |
|--------------|--|---------------|------|--|
| UE 038 | test tube rack stainless steel | 12 | 20 | |
| suitable for | 1 x in AL 5 3 x in AL 12 6 x in AL 18, AL 25 | | | |



Platform

Stainless steel up to 100 °C, with eight height adjustable steps

| CatNo.: | Usable area mm | |
|--------------|-------------------------------------|--|
| LCZ 0689 | 140x270 | |
| suitable for | 1 x in AL 12 2 x in AL 18, AL 25 | |





Order the detailed LAUDA accessories brochure and the heat transfer liquids brochure free of charge. This and additional product information can also be found at www.lauda.de